
Wintouch Shenzhen United Touch Technology Co., LTD

st Building, Boshi Industrial Park, Huake Zone, Shida Road, Dalingshan Town, Dongguan City, Guangdong Prov..P.R.China

Contact: Ken Chen E-mail: ken@unitedtouch.cn Mobile: +86 13922898904 Website: http://www.uniontouch.com/ http://unitedtouch.en.alibaba.com/

13.3inch Capacitive Touch Android PC

- · Edge-to-edge glass IP65 rated
- •10-finger multitouch touch screen Panel
- RK3568/2G/16G/
- 2GB RAM
- 16GB SSD included
- 32Bit and 64Bit support, Android 11
- Integrated Wi-Fi, 1× LAN
- VESA 75 bracket for mounting, metal stand included
- Customization available upon request



The Touchscreen PC features a sleek modern appearance. Flat edge to edge glass with a patented silicone rubberized seal ensures the front panel is water proof and dust proof meeting the requirements of IP65 standards. The back has a sturdy aluminum case manufactured out of a continuous casting mold with stable VESA-75/100 fixation bolts offering numerous industrial and consumer connectors like serial ports or USB 3.0.

The heart of the Touchscreen PC mainboard with the powerful but fanlessly cooled MT8735, Quad-Core processor, equipped with 1GB RAM, 8G SSD

The capacitive touch panel is completely inhouse developed by Wintouch's renowned engineers. it can be Anti Glare chemically etched surface treatment, 10-finger multitouch and unlimited touches without failure on the touch panel are class leading features. Behind that touch panel are wintouch's A+ panels, guaranteeing that there is not even a single sub-pixel defect.

Wintouch's industrial touch PCs ensure the performance and stability required for long term operation in today's demanding manufacturing, commercial, and retail environments.



















Product name	13.3" PCAP Touch PC	
Modle numer	WTPA133-3568	
Anti-glare LCD Panel		
IP rated front panel	IP65	
Screen diagonal (Inch/cm):	13.3	
Display active screen size:	304x177mm	
Aspect ratio:	16:10	
Physical resolution:	1920x1080	
Colours displayed:	16M	
Brightness (cd/m2):	400	
Contrast:	800:1	
Typical reaction time Tr/ Tf :	10/15 (ms)	
Visual Angle horizontal/vertical :	170/170(°)	
Backlight / Backlight Lifetime	LED / 30,000	

Operation / Mechanical		
Operating Temperature	-20 ~ +70 (°C)	
Humidity Range (RH)	10%-90%	
Gross weight (kg)	2	
Housing material	metal	
Housing (cm) LxWxH	28.4*17.5*3.55	
Mounting	VESA 75	

PC System		
CPU	RK3568	
Memory	2G	
Storage	16GGB	
USB Port	1*USB 2.0 2*USB3.0	
HDMI	1	
I/O	RJ45+HDMI	
GPIO	Support 3 chanel GPIO	
Wifi/Buletooth/NFC	Support	
System	Android 11	

Touch Panel		
Touch Technology	Projected Capacitive 10-point Multitouch	
Touch Connector	USB	
Touch Panel Drivers	Windows; Linux; Mac; Android	
Touch Life (Contacts)	Unlimited	
Surface Hardness	7H	

Power	
Power Indicator	Green LED
Power Supply	100-240V ACDC active switching; 12V DC-Out
Working Power (V)	12
Power Consumption	11
Stand-By Consumption (W)	<1