

- •10-finger multitouch touch screen Panel
- Android RK 3566
- 2GB RAM, 16GByte SSD included
- Android version 11
- •Integrated Wi-Fi and network ports.
- VESA 100 bracket for mounting, metal stand included
- Customization available upon request

Wintouch's innovative IP65 Front Capacitive Touchscreen PC with its silent fanless operation, reliability, and fine craftsmanship, stands out from the competition.

The Touchscreen PC features a sleek modern appearance. Flat edge to edge glass with a patented silicone rubberized seal ensures the front panel is water proof and dust proof meeting the requirements of IP65 standards. The back has a sturdy aluminum case manufactured out of a continuous casting mold with stable VESA-75 fixation bolts offering numerous industrial and consumer connectors like serial ports or USB 3.0.

The heart of the Touchscreen PC is Android RK 3566mainboard, equipped with 2GB RAM, 16G SSD

The capacitive touch panel is completely inhouse developed by Wintouch's renowned engineers. it can be Anti Glare chemically etched surface treatment, 10finger multitouch and unlimited touches without failure on the touch panel are class leading features. Behind that touch panel are wintouch's A+ panels, guaranteeing that there is not even a single sub-pixel defect. As an option, customers can chose optical bonding and high brightness panels to further improve the visual impression of the product.

Wintouch's industrial touch PCs ensure the performance and stability required for long term operation in today's demanding manufacturing, commercial, and retail environments.



















Product name	7" PCAP Touch PC		
Modle numer	WTPC070		
Anti-glare LCD Panel			
IP rated front panel	IP65		
Screen diagonal (Inch/cm):	7/17.78		
Display active screen size:	15.36x9.00		
Aspect ratio:	16:9		
Physical resolution:	1024x600		
Colours displayed:	16.7M		
Brightness (cd/m2):	300		
Contrast:	700:1		
Typical reaction time Tr/ Tf :	10/15 (ms)		
Visual Angle horizontal/vertic	cal : 150/145		
Backlight / Backlight Lifetime	ED / 30,000		

Operation / Mechanical	
Operating Temperature	-10 ~ +65 (°C)
Humidity Range (RH)	10%-90%
Net weight (kg)	0.6
Gross weight (kg)	2 (incl. cartonage)
Housing material	Aluminium
Housing (cm) LxWxH	18.25x12.95x3.53
Mounting	VESA 75

PC System		
CPU	Android RK 3566	
Memory	2GB RAM	
Storage	16GB SSD	
W-LAN	1x LAN	
Driver Support	Android	

Touch Panel		
Touch Technology	Projected Capacitive 10- point Multitouch	
Touch Connector	USB	
Touch Panel Drivers	Windows; Linux; Android	
Touch Life (Contacts)	Unlimited	
Surface Hardness	7H	

Power		
Power Indicator	Green LED	
Power Supply	100-240V ACDC active switch- ing; 12V DC-Out	
Stand-By Consumption	<0.5	

External Connectors		
2*USB	1*HDMI	
1*RS232	1*LAN	
1*WIFI		











Sunny Yu

Email: Sunny@unitedtouch.cn

MP: +86 15800041166 Skype: Sunny@unitedtouch.cn www.unitedtouch.en.alibaba.com www.wintouch.cc Shenzhen United Touch Technology Company Co.,Ltd

3F, 1st Building, Boshi industrial park, HuaKe zone, Shida Road, Dalingshan, Dongguan, Guangdong Prov., P.R.